



TOA ELECTRONICS, INC.

601 Gateway Boulevard, Suite 300
 South San Francisco, California 94080
 Telephone (650) 588-2538 Fax (650) 588-3349
<http://www.toaelectronics.com>



PREMIUM LINE LCD CCTV MONITOR

Spec

19RTC

Display	Screen Size	19"
	Viewing Area	376.0 x 301.0 mm
	Pixel Type	Active Matrix TFT
	Max. Resolution	1280 x 1024 @60Hz
	Pixel Pitch	0.294 x 0.294 mm
	Brightness	300cd/m ²
	Contrast Ratio	1000:1
	Aspect Ratio	5 : 4
	Viewing Angle(H/V)	160°/160°
	Display Color	16.7 Million
	Response Time	< 5ms
	Video System	NTSC / PAL
	Frequency(H)	31 ~ 64 KHz(H)
	Frequency(V)	55 ~ 75 KHz(V)
Audio	Built in Speakers	Yes(2W X 2)
	Gradual Volume Increase	YES
Interface	Video In/ Out(BNC Type)	2 / 2
	S-Video In/ Out	1 / 1
	RGB In(15Pin D-Sub)	1
	Component	1
	DVI In/ HDMI In	1 / 1
	Audio In/ Out(RCA Type)	39114
	PC Stereo In	1
Transmitter	Remote Control	Yes
Special Features	Multi Display Function	PIP / PBP
	Filter Type	3D Comfilter / DeInterace
	LCD Protection Glass	Yes
	Rack Mountable Kit	Optional(Wall, Rack, Swing Arm)
	Camera Mounting Hole	2(Upper / Bottom)
	Multi-lingual Language	English, Spanish, French, German, Italian, Portuguese, Nederland
	VESA™ DDC Compatible	Yes
Dimension	Outline Dimension	428.5 x 380.2 x 83 mm
	Packaging Dimension	540 x 485 x 180 mm
	Net Weight	7.5Kg (16.5lbs)
	Gross Weight	9Kg (19.8lbs)
Cabinet	Finish/Tilt Stand	Black/Yes
Mounts	VESA Mounts Size	100 x 100 mm (BS M4 x 10 mm Screw)
Warranty	Parts/ Labor	1 Year / 1 Year
	MTBF(Approx.)	50,000 Hours
Power	Regulations	TUV-NRTL(=UL), CB, FCC(A), CE-Emc(LVD)
	Consumption : < On / < Stand-by	<45W
	Electrical Ratings	AC100 ~ 240V(50/60Hz) DC 12V / 4,12A Adapter
Circumstance	Operating Temperature	10 ~ 40°C / 50 ~ 104°F