

### DESCRIPTION

The S-20S is EV module to be used in conjunction with the 900 series and BG-1000 series amplifier and VX-2000.

Up to 4 types of music and messages (6 minutes total time) can be recorded and played back.

The USB port facilitates recording by transferring the supplied sound sources from a PC to the unit.

### SPECIFICATIONS

\* 0 dB = 1 V

Power Source	24 V DC
Current Consumption	Under 40 mA
Output	0 dB*
Wave Format	44.1 kHz sampling frequency, 16-bit PCM (monaural)
Frequency Response	50 Hz - 20 kHz $\pm 3$ dB (1 kHz)
Distortion	Under 1 % (1 kHz)
Recording System	USB data transfer
Control Input	Play 1-4, stop: No-voltage make contact input, pulse make length: 200 ms, open voltage: 24 V DC, short-circuit current: 2 mA removable terminal block (6 pins)
Maximum No. of Messages	4
Maximum Recording Time	6 min
Playback Interval Time	$\infty$ , 0 s, 5 s, 10 s, 30 s, 1 min, 5 min, 10 min, 30 min or 1 h (selectable)
Operating Temperature	0 °C to +50 °C
Finish	Panel: Aluminum, hairline
Dimensions	35 (W) x 78 (H) x 88 (D) mm
Weight	65 g
Accessory	CD-ROM (USB data transfer software and sample chimes recorded) $\times 1$ , USB cable (1 m) $\times 1$ , Removable terminal plug (6 pins) $\times 1$ , Mounting screw $\times 2$
Applicable Model (option)	A-900 series, BG-1000 series, VX-2000

### USB Data Transfer Software Operation Environment

Personal Computer	IBM-AT compatible type (equipped with the USB terminal)
Main Specifications	CPU: Pentium compatible CPU of 133 MHz or more Memory: Over 64 MB (recommended: 128 MB or more) Free disk space: Over 10 MB (space for message storage excluded)
OS	Windows 2000/XP (32-bit edition)/Vista (32-bit edition)

Notes: Pentium is a trademark of Intel Corporation.

Windows is a trademark of Microsoft Corporation.

Other company names and products are also trademarks of individual companies.

### APPEARANCE

